



“NJN” Ltd.

6300 Haskovo, Square "City Hospital" №1
„Complex 21st Century“, 4th floor, office 5

ANNEX 1

Certificate of Conformity of the Factory Production Control № 1888 – CPR – 3564

100x390x190mm

Essential characteristics	Performance		Harmonized Standard
Compressive strength	Compressive strength	3,09N/mm ² (indication of direction of load and unit category)	EN 771-3:2011
Bond strength	Bond strength	0,15 N/mm ²	
Water absorption	Water absorption	Declared text: "Not to be left exposed"	
Direct airborne sound insulation	Gross density	874 kg/m ³	
	Configuration	Declared configuration as illustrated or described	
	Dimensions and tolerances	100x390x190 D1	
Durability against freeze/thaw	Durability	Declared text: "Not to be left exposed"	

135x390x190mm

Essential characteristics	Performance		Harmonized Standard
Compressive strength	Compressive strength	2,86N/mm ² (indication of direction of load and unit category)	EN 771-3:2011
Bond strength	Bond strength	0,15 N/mm ²	
Water absorption	Water absorption	Declared text: "Not to be left exposed"	
Direct airborne sound insulation	Gross density	739 kg/m ³	
	Configuration	Declared configuration as illustrated or described	
	Dimensions and tolerances	135x390x190 D1	
Durability against freeze/thaw	Durability	Declared text: "Not to be left exposed"	

150x390x185mm

Essential characteristics	Performance		Harmonized Standard
Compressive strength	Compressive strength	3,01N/mm ² (indication of direction of load and unit category)	EN 771-3:2011
Bond strength	Bond strength	0,15 N/mm ²	
Water absorption	Water absorption	Declared text: "Not to be left exposed"	
Direct airborne sound insulation	Gross density	712 kg/m ³	
	Configuration	Declared configuration as illustrated or described	
	Dimensions and tolerances	150x390x185 D1	
Durability against freeze/thaw	Durability	Declared text: "Not to be left exposed"	

NB 1888

